

DATA SHEET

PRIMERGY TX200 S4

Issue: February 2009

Dual Socket Quad-Core Intel® Xeon® Server - Cost-efficient expansion options and failsafe operation

PRIMERGY TX Tower Servers deliver highest reliability rates with proven data center technology comparable with high end UNIX servers. The innovative, broadest portfolio of virtualization, server and solution offerings stand for TCO reductions of 60% or more. Optimized air flow cooling technology assures a long life and highest possible performance/watt at work as well as by far best in class efficiency proven by numerous benchmark records. And as your business grows, plenty of headroom for expansion protects your investments in PRIMERGY as well as our universal tower-to-rack conversion kit does in case of consolidation changes. PRIMERGY ServerView Suite with remote management functions provides comprehensive management from anywhere at any time.

The flexible custom supply model and our build-to-order process mean, that only fully built and pre-tested solutions are shipped to customers. Last but not least Fujitsu Technology Solutions proven commitment to green IT offers clear competitive advantages to our customers.

PRIMERGY TX200 S4

Flexible expansion options are the key to placing new or larger workloads on your server. This applies not only to physical capacity, such as the number of disk drives, advanced data protection schemes, or I/O connectivity; in particular consideration of the transition to 64-bit computing and virtualization is a must in today's technology purchase decisions.

The PRIMERGY TX200 S4 uses a completely new housing and is a perfect match for these requirements, providing you with a previously unreachable cost-efficient standard. TX200 is a failsafe operation platform for your application stacks, with standards such as disk mirroring for SAS and SATA, hot-plug disks, SDDC and hot-spare memory and the "Cool-safe™" innovative air flow system design. Expandability is covering for heavy workload: up to 24 GB FBD667 memory, up to 8 (16) 2.5-inch SAS hard disk drives, and 7 (6) free PCI slots for heavy I/O requirements. Your business can rely on this solution!

In addition, further options – such as extended RAID functions, clustering options and redundancy for power supplies and fans – tailor these standards to your individual safety needs.



MAIN FEATURES	BENEFITS
ECC, built-in RAID 1 functionality and optional ibutton RAID 5 for SATA or modular RAID for SAS configurations	High security against physical loss of data
Hot-plug HDD infrastructure (standard), Hot-plug redundant PSU (optional) Redundant fans (optional), ServerView Local Service Panel (LSP) (optional)	Tailor made availability, offers the security level which is recommended by your individual application demands
Energy efficient Intel Quad-Core processor (5400 series), provides four execution cores (2x 6 MB Cache) in one physical processor with less power consumption	Allowing the platform to do more in less time, IT departments can consolidate applications and more effectively employ the server with less power consumption
Up to 4x SATA or 4 (6)x SATA/SAS 3.5-inch, up to 8 (16)x 2.5-inch SAS hard disks, 7 PCI/PCIe slots, (6 with SAS), 1x Gbit LAN plus extra Service LAN for iRMC S2	Expandability options for further growth



Technical details

Mainboard

Mainboard type	D 2509
Chipset	Intel® 5000Z
Processor quantity and type	1 - 2 x Intel® Xeon® processor 5200 / 5300 / 5400 series

Processor options

Intel® Xeon® E5205 (2C, 1.86 GHz, SLC: 6 MB, 1066 MHz, 65 W)
Intel® Xeon® E5405 (4C, 2.00 GHz, SLC: 2 x 6 MB, 1333 MHz, 80 W)
Intel® Xeon® E5420 (4C, 2.50 GHz, SLC: 2 x 6 MB, 1333 MHz, 80 W)
Intel® Xeon® E5430 (4C, 2.66 GHz, SLC: 2 x 6 MB, 1333 MHz, 80 W)
Intel® Xeon® L5310 (4C, 1.60 GHz, SLC: 2 x 4 MB, 1066 MHz, 50 W)
Intel® Xeon® L5410 (4C, 2.33 GHz, SLC: 2 x 6 MB, 1333 MHz, 50 W)
Intel® Xeon® L5420 (4C, 2.50 GHz, SLC: 2 x 6 MB, 1333 MHz, 50 W)

Memory slots	6 (3 Banks with 2 slots each)
Memory slot type	PC2-5300F (Fully buffered DIMM DDR2 667 ECC)
Memory capacity (min. - max.)	1 GB - 24 GB
Memory Protection	Advanced ECC SDDC (Chipkill™) Memory Scrubbing Hot-spare memory support

Memory options

8 GB (2 module(s) with 4 GB), FB-DIMM (DDR2), 667 MHz, PC2-5300F	
4 GB (2 module(s) with 2 GB), FB-DIMM (DDR2), 667 MHz, PC2-5300F	
2 GB (2 module(s) with 1 GB), FB-DIMM (DDR2), 667 MHz, PC2-5300F	
1 GB (2 module(s) with 512 MB), FB-DIMM (DDR2), 667 MHz, PC2-5300F	
Upgrade notes	For a memory and processor upgrade a BIOS update may be required.

Interfaces

USB ports	5 x USB 2.0 (1x front, 2x rear, 2x internal)
Graphics (15-pin)	1 x VGA
Serial 1 (9-pin)	1 x serial RS-232-C, usable for iRMC S2 or system or shared
Serial 2 (9-pin)	1 x serial RS-232-C
Parallel (25-pin)	1 x Centronics 25-pin EPP/ECP compatible (option)
Mouse / Keyboard (PS/2)	2
LAN / Ethernet (RJ-45)	1 x Gbit/s Ethernet
Service LAN (RJ45)	1 x dedicated service LAN port for iRMC S2 (10/100 Mbit/s) Service LAN traffic can be switched to shared onboard Gbit LAN port

Onboard or integrated Controller

RAID Controller	Integrated RAID 0/1 or RAID 5/6 controller for SAS base units (occupies one PCIe slot). See under Components RAID controller
SATA Controller	6311ESB, 6-port SATA (4x internal HDDs in SATA base units with RAID 0/1/10 and 2x for accessible drives)
SATA Controller type notes	optional RAID 5 (iButton key) SATA SW RAID support for Windows and Linux OS only
LAN Controller	BCM 5708, 10/100/1000 Mbit/s Ethernet, TCP/IP acceleration, PXE-Boot via LAN from PXE server, iSCSI Boot (also diskless) via onboard LAN
Remote Management Controller	Integrated Remote Management Controller (iRMC S2, 32 MB attached memory incl. graphics controller), IPMI 2.0 compatible
Onboard Controller notes	For detailed information please refer to the corresponding system configurator.

Slots

PCI-Express x4 (mech. x8)	4 x (2 slots x8 with performance adapter option) 2 x long (1x for modular SAS RAID controller)
PCI slots	1 x 32bit/ 33MHz, 5V

Slots	
PCI-X	2 x 64-bit / 100 MHz, 3.3 V, long (1 x with max. 133 MHz (IOOP™), if only 1 Slot is occupied)
Slot Notes	in SAS configuration 1x PCI-Express occupied by modular RAID controller
Drive bays	
Accessible drive bays	3 x 5.25/1.6-inch 1 x 3.5/1-inch for FDD
Notes accessible drives	All possible options described in relevant system configurator 2x 3,5-inch HDD box only in SAS configuration
Fan Configuration	
Fan configuration	3 non hot-plug fans as standard, fan redundancy as option (3+1)
Operating panel	
Operating buttons	On/off switch NMI button Reset button
Status LEDs	System status (amber / yellow) Identification (blue) Hard disks access (green) Power (amber / green) At system rear side: System status (amber / yellow) Identification (blue) LAN connection (green) LAN speed (green / yellow)
Service display	Optional: ServerView Local Service Panel (LSP)
BIOS	
BIOS features	ROM based setup utility Recovery BIOS BIOS settings save and restore Local BIOS update from USB device Online update tools for main Windows and Linux versions Local and remote update via ServerView Update Manager SMBIOS V2.4 Remote PXE boot support Remote iSCSI boot support
Supported operating systems	
Supported operating systems	Microsoft® Windows Server® 2008 Microsoft® Windows Server® 2003 Novell SUSE Linux Enterprise Server Red Hat Enterprise Linux VMware Infrastructure Note: Support of other Linux derivatives on demand
Operating system release link	http://ts.fujitsu.com/software ftp://ftp.ts.fujitsu.com/outgoing/osrel.xls
Server Management	
Standard	ServerView Deployment Manager (fully functional 30-day trial version) ServerView Integration solutions for Microsoft SMS, MOM, SCOM, SCCM and Altiris Deployment Solution Online update packages for BIOS, firmware drivers and ServerView Agents ServerView Suite: SV Installation Manager SV Operation Manager SV RAID Manager SV Update Manager SV Agents
Option	ServerView Deployment Manager (fully functional unlimited version) ServerView Remote Management ServerView Integration for Tivoli TEC®, Tivoli NetView, HP OpenView NNM and HP OpenView iRMC S2 Advanced Pack
Server Management Notes	Regarding Operating System dependencies and product details for ServerView Suite Software Products see dedicated Product Data sheets.

Dimensions / Weight

Dimension notes	Width 372 mm with tilt protection
Weight	up to 35 kg
Weight notes	Weight may vary depending on actual configuration
Rack integration kit	Rack integration kit as option

Environmental

Noise emission	Measured according to ISO 7779 and declared according to ISO 9296
Sound pressure (LpAm)	35 dB(A) (idle) / 37 dB(A) (operating)
Sound power (LWAd; 1B = 10dB)	5.3 B idle (idle) / 5.4 B (operating)
Noise notes / description	only with standard fans and standard PSU
Operating ambient temperature	10 - 35°C
Operating relative humidity	10 - 85 % (non condensing)

Electrical values

Power supply configuration	Base unit specific: 1x standard power supply or 2x hot-plug power supply (1 + 1 redundancy)
Rated voltage range	100 - 127 V / 200 - 240 V
Rated frequency range	50 - 60 Hz
Rated current max.	9.0 A / 4.5 A (100 V / 240 V)
Rated current in basic configuration	2.0 A / 0.86 A (100 V / 240 V)
Active Power max. (per system unit)	512 W
Apparent power max. (per system unit)	531 VA
Heat emission	1843.2 kJ/h (1747.4 BTU)

Compliance

Germany	GS
Europe	CE
USA/Canada	CSAc/us ULc/us FCC Class A
Global	CB RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment)
Japan	VCCI
Australia&New Zealand	C-Tick
Taiwan	BSMI
Compliance notes	There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request.
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/default.aspx

Components

Hard disk drives	SATA, 3 Gb/s 1000 GB, 7200 rpm, hot plug, 3.5-inch SATA, 3 Gb/s 750 GB, 7200 rpm, hot plug, 3.5-inch SATA, 3 Gb/s 500 GB, 7200 rpm, hot plug, 3.5-inch SATA, 3 Gb/s 250 GB, 7200 rpm, hot plug, 3.5-inch SATA, 3 Gb/s 160 GB, 7200 rpm, hot plug, 3.5-inch SAS, 3 Gb/s 300 GB, 15000 rpm, hot plug, 3.5-inch SAS, 3 Gb/s 146 GB, 15000 rpm, hot plug, 3.5-inch SAS, 3 Gb/s 146 GB, 10000 rpm, hot-plug, 2.5-inch SAS, 3 Gb/s 73 GB, 15000 rpm, hot plug, 3.5-inch SAS, 3 Gb/s 73 GB, 10000 rpm, hot-plug, 2.5-inch
Hard disk notes	Mix of 3.5-inch SAS and SATA HDD requires separate HDD cages and RAID sets One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. Accessible capacity may vary, also depending on used software

Tape Drives	DDS Gen5, 36 GB , 3 MB/s, half height, SCSI U2W
	DDS Gen5, 36 GB , 3 MB/s, half height, USB 2.0
	DDS Gen5 OBDR, 36 GB , 3 MB/s, half height, SCSI U2W
	DDS Gen6, 80 GB , 6 MB/s, half height, SCSI U160
	DDS Gen6, 80 GB , 6 MB/s, half height, USB 2.0
	LTO2HH Ultrium LC, 200 GB , 24 MB/s, half height, SCSI U160
	LTO3HH Ultrium, 400 GB , 60 MB/s, half height, SCSI U320
	LTO4HH Ultrium, 800 GB , 120 MB/s, half height, SAS 3Gb/s
	RDX Drive, 80 GB, 160 GB, 320 GB , 25 MB/s, half height, USB 2.0
Optical drives	Blu-ray combo drive, (2x BD-ROM; 8x DVD; 24x CD), slimline, SATA I
	Blu-ray combo drive, (6x BD-ROM; 16x DVD; 40x CD), half height, SATA I
	CD-RW / DVD Combo, (8x DVD; 24x CD/CD-R, 16x CD-RW), slimline, SATA I
	DVD-ROM, (16xDVD; 48xCD), half height, SATA I
	DVD Super Multi, (16xDVD, 8xDVD+RW 6xDVD-RW, 12xDVD-RAM; 48xCD, 32xCD-RW), half height, SATA I
	DVD Super Multi, (8x DVD/DVD+RW, 6x DVD-RW, 5x DVD-RAM; 24x CD/CD-R, 16x CD-RW), slimline, SATA I
SCSI / SAS Controller	SCSI Ctrl 320 MB 1ch int/ext PCIe x1
	SAS Ctrl 3 Gb 4 ports int. / 4 ports ext. PCIe x4
RAID Controller	RAID 5/6 Ctrl, SAS/SATA 3 Gb, LSI MegaRAID SAS8880E, 8 ports ext. RAID level: 0, 1, 10, 5, 50, 6, 60, 512 MB Cache, no BBU support (based on LSI 1078)
	RAID 5/6 Ctrl, SAS/SATA 3 Gb, LSI MegaRAID SAS8880E, 8 ports ext. RAID level: 0, 1, 10, 5, 50, 6, 60, 512 MB Cache, inclusive BBU (based on LSI 1078)
	Integrated SW RAID 5, SATA II 3 Gb, LSI Embedded MegaSR RAID5, RAID level: 0, 1, 10, no BBU support
	Integrated RAID 5/6 Ctrl, SAS/SATA 3 Gb, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 512 MB Cache, optional BBU (based on LSI 1078)
	Integrated RAID 5/6 Ctrl, SAS/SATA 3 Gb, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 256 MB Cache, optional BBU (based on LSI 1078)
	Integrated RAID 0/1 Ctrl, SAS/SATA 3 Gb, 8 ports int. RAID level: 0, 1, 1E, no BBU support (based on LSI 1068e)
	Integrated RAID 0/1 Ctrl, SAS/SATA 3 Gb, 4 port int. RAID level: 0, 1, 1E, no BBU support , for internal SAS tapes (based on LSI 1064e)
Fibre Channel controller	Fibre Channel Ctrl 1 x 4 Gb Emulex LPe1150 MMF LC
	Fibre Channel Ctrl 2 x 4 Gb Emulex LPe11002 MMF LC
	Fibre Channel Ctrl 1 x 4 Gb Qlogic QLE2460 MMF LC
	Fibre Channel Ctrl 2 x 4 Gb Qlogic QLE2462 MMF LC
	Fibre Channel Ctrl 2 x 8 Gb Emulex LPe12002 MMF LC
	Fibre Channel Ctrl 1 x 8 Gb Emulex LPe1250 MMF LC
LAN Controller	Ethernet Ctrl 1 x 1 Gb Intel® Gigabit CT Desktop Adapter
	Ethernet Ctrl 1 x 1 Gb Intel® PRO/1000 GT Desktop Adapter
	Ethernet Ctrl 1 x 1 Gb Intel® PRO/1000 MT Single Port Server Adapter
	Ethernet Ctrl 1 x 1 Gb Intel® PRO/1000 PF Server Adapter
	Ethernet Ctrl 1 x 1 Gb Intel® PRO/1000 PT Server Adapter
	Ethernet Ctrl 2 x 1 Gb Intel® PRO/1000 GT Dual Port Server Adapter
	Ethernet Ctrl 2 x 1 Gb Intel® PRO/1000 PT Dual Port Server Adapter
	Ethernet Ctrl 4 x 1 Gb Intel® PRO/1000 PT Quad Port Server Adapter
Rack infrastructure	Rackmount kit sliding drawer, full extraction, cable management
Warranty	
	Standard Warranty 3 years
Service level On-site Service	
Maintenance and Support Services - the perfect extension	
Recommended Service 7x24, Onsite Response Time: 4h	
Spare Parts availability 5 years	
Service Weblink http://ts.fujitsu.com/Supportservice	

Information about environmental care, policies, programs and our Environmental Guideline FSC 03230:

<http://ts.fujitsu.com/aboutus>

Take back and Recycling information:

<http://ts.fujitsu.com/recycling>

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions February 2009

Published by
Fujitsu Technology Solutions
<http://ts.fujitsu.com/>